

Brite Gard 100

Synthetic-based Corrosion Preventative for Compressors & Equipment

Applications:

Brite Gard 100 is a special lubricant blend which is designed to preserve pump and compressor equipment from rusting while in transit to the customer site and in warehouse storage. This synthetic blend includes penetrating compounds and vapor phase corrosion inhibitors to provide adherence to metal surfaces. This preservative offers good anti-wear and corrosion inhibition properties and is an excellent coating for initial start-up lubrication in the field. Brite Gard 100 is compatible with typical mineral based compressor and pump lubes and most synthetic based fluids.

Typical Industrial Applications:

- Compressors
- Pumps
- Blowers
- Separator Vessels
- Enclosed Gear Boxes

Performance Benefits:

- Prevents rusting during transportation and storage
- Provides start-up lubrication and wear protection
- Provides compatibility with typical compressor/pump lubricants
- Offers easy application by filling and drain, or internal spraying.

TYPICAL PROPERTIES	TEST METHOD	Brite Gard 100
ISO Grade	ASTM D2422	100
Viscosity @ 40 °C, cSt	ASTM D445	100
Viscosity @ 100 °C, cSt	ASTM D445	11.8
Viscosity Index	ASTM D2270	108
Flash Point, °C/°F	ASTM D92	221/430
Pour Point, °C/°F	ASTM D97	-30/-22
Copper Corrosion	ASTM D130	1b
Specific Gravity	ASTM D1298	0.87

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com