

CHEMLUBE® 224

SYNTHETIC HIGH TEMPERATURE CHAIN LUBRICANT

Applications:

Chemlube 224 is a fully synthetic diester-based chain lubricant designed for use in high temperature applications and harsh environmental conditions. Chemlube 224 gives extended life in the temperature range of -10 F to 425 F and will reduce carbon, gum or sludge deposits. This chain oil has a low evaporation rate making it last longer and has outstanding wetting and spreading properties. With these properties, Chemlube 224 yields savings in maintenance dollars.

Typical Industrial Applications:

- Conveyors
- Lateral Chain Belts
- Tunnel / Lap / Tray Ovens
- Cam
- Bearings
- High Speed Can Lines
- Oven Slides & Gears
- Conveyor Roller Ball Bearing Chains
- Wood Processing
- Coating Ovens Automotive Industry

Performance Benefits:

- Superior resistance to wear
- Highest degree of high temperature corrosion-oxidation stability
- Reduced maintenance cost & cleanliness
- Non-slinging

TYPICAL PROPERTIES	TEST METHOD	Chemlube 224
Viscosity @ 40°C,cSt	ASTM D445	204.1
Viscosity @ 100°C,cSt	ASTM D445	27.4
Viscosity Index	ASTM D2270	171
Flash Point, °C/°F	ASTM D92	240/465
Pour Point, °C/°F	ASTM D97	-29/-20
Auto Ignition, °C/°F	ASTM E659	407/765
Lbs./Gal.	---	7.96
Specific Gravity	ASTM D1298	0.96

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com