

## CHEMLUBE® 226

### SYNTHETIC HIGH TEMPERATURE CHAIN LUBRICANT

#### Applications:

Chemlube 226 is a fully synthetic fluid designed for use as a high temperature, polymer-free chain lubricant with an organic molybdenum compound to give superior wear protection. This premium chain oil has the advantage of being easily applied through a mister or atomizer type lubricators due to its viscosity grade. Chemlube 226 gives extended life in the temperature range of -20°F to 500°F and will reduce carbon, gum or sludge deposits. It also has a low evaporation rate making it last longer and has outstanding wetting and spreading properties. With these properties, Chemlube 226 yields savings in maintenance dollars.

#### Typical Industrial Applications:

- Conveyors
- Lateral Chain Belts
- Tunnel / Lap / Tray Ovens
- Cam
- Bearings
- High Speed Can Lines
- Lithographic Chains
- Oven Slides & Gears
- Conveyor Roller Ball Bearing Chains
- Gypsum Board Processing
- Fiberglass Processing
- Wood Processing
- Coating Ovens Automotive Industry

#### Performance Benefits:

- Superior resistance to wear
- High degree of high temperature corrosion-oxidation stability
- Reduced maintenance cost & cleanliness
- Natural detergency eliminates deposits
- Superior lubricity provides an end to chain kinking or shortening

TYPICAL PROPERTIES	TEST METHOD	Chemlube 226
ISO Grade	ASTM D2422	46
SAE Grade	SAE J-300	20
Viscosity @ 40°C,cSt	ASTM D445	41.3
Viscosity @ 100°C,cSt	ASTM D445	7.8
Viscosity Index	ASTM D2270	163
Flash Point, °C/°F	ASTM D92	260/500
Pour Point, °C/°F	ASTM D97	-46/-50
Fire Point, °C/°F	ASTM D92	296/565
Auto Ignition Temp., °C/°F	ASTM D2155	418/785
Lbs./Gal.	---	7.54
Specific Gravity	ASTM D1298	0.90

#### HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

#### TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at [info@ultracheminc.com](mailto:info@ultracheminc.com)



900 Centerpoint Blvd.  
New Castle, DE 19720  
P.....302-325-9880  
F.....302-325-0335  
[info@ultracheminc.com](mailto:info@ultracheminc.com)