

## CHEMLUBE® 275

### SYNTHETIC HIGH TEMPERATURE CHAIN LUBRICANT

#### Applications:

Chemlube 275 is a fully synthetic diester-based chain lubricant designed for use in high temperature applications and harsh environmental conditions. This premium chain oil contains soluble organic compounds for added wear protection. Chemlube 275 gives extended life in the temperature range of -10°F to 450°F and will reduce carbon, gum or sludge deposits. It also has a low evaporation rate making it last longer and has outstanding wetting and spreading properties. With these properties, Chemlube 275 yields savings in maintenance dollars.

#### Typical Industrial Applications:

- Textile Tenter Frames
- Conveyors
- Lateral Chain Belts
- Tunnel / Lap / Tray Ovens
- Cam
- Bearings
- High Speed Can Lines
- Oven Slides & Gears
- Conveyor Roller Ball Bearing Chains
- Wood Processing
- Coating Ovens Automotive Industry

#### Performance Benefits:

- Superior resistance to wear
- Highest degree of high temperature corrosion-oxidation stability
- Reduced maintenance cost & cleanliness
- Non-slinging

TYPICAL PROPERTIES	TEST METHOD	Chemlube 275
ISO Grade	ASTM D2422	320
Viscosity @ 40°C,cSt	ASTM D445	320
Viscosity @ 100°C,cSt	ASTM D445	22.5
Viscosity Index	ASTM D2270	85
Flash Point, °C/°F	ASTM D92	274/525
Pour Point, °C/°F	ASTM D97	-28/-20
Fire Point, °C/°F	ASTM D92	282/540
Specific Gravity	ASTM D1298	0.94

#### HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

#### TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at [info@ultracheminc.com](mailto:info@ultracheminc.com)



900 Centerpoint Blvd.  
New Castle, DE 19720  
P.....302-325-9880  
F.....302-325-0335  
[info@ultracheminc.com](mailto:info@ultracheminc.com)