

CHEMLUBE® CV

CENTRIFUGAL COMPRESSOR LUBRICANT

Applications:

Chemlube CV is a fully synthetic diester -based lubricant designed for use in centrifugal air compressors. Chemlube CV is formulated from with premium polyolester base oil and excellent antioxidants and anti-wear additives.

Typical Industrial Applications:

- Centrifugal Compressors
- Vacuum Pumps

Performance Benefits:

- Outstanding thermal and oxidative stability
- Superior anti-wear protection
- Excellent low temperature properties
- High flash point means increased safety
- Caution: May affect some paint finishes, plastics and seals

TYPICAL PROPERTIES	TEST METHOD	Chemlube CV
ISO Grade	ASTM D2422	15
Viscosity @ 40°C,cSt	ASTM D445	14
Viscosity @ 100°C,cSt	ASTM D445	3
Viscosity Index	ASTM D2270	120
Flash Point, °C/°F	ASTM D92	230/446
Pour Point, °C/°F	ASTM D97	-65/-85
Specific Gravity	ASTM D1298	0.95

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com