

CHEMLUBE[®] 315 IMPREGNATING LUBRICANT

Applications:

Chemlube 315 is a fully synthetic premium lubricant to use in industrial low temperature applications and as an impregnating lubricant for the powder metal industry.

Minimum Order: (55) gallon drum

Typical Industrial Applications:

- Impregnating Lubricant
- Instruments
- Meters
- Outdoor Controls
- Motors
- Powder Metal Bearings
- Ball Bearings
- Slides

Performance Benefits:

- Very light viscosity for best low temperature operation
- Excellent oxidation stability, no deposits
- Very low torque requirement
- Extreme long life
- Wide temperature range, -100 to 250°F

TYPICAL PROPERTIES	TEST METHOD	Chemlube 315
Viscosity @ 40°C,cSt	ASTM D445	5.07
Viscosity @ 100°C,cSt	ASTM D445	1.75
Viscosity @ -40°C,cSt	ASTM D445	152
Flash Point, °C/°F	ASTM D92	182/360
Pour Point, °C/°F	ASTM D97	-76/-105
Evaporation, %	ASTM D972	3.9
Lbs./Gal.	---	7.21
Specific Gravity @ 20°C	ASTM D1298	0.864
Specific Gravity @ 50°C	ASTM D1298	0.841
Specific Gravity @ 100°C	ASTM D1298	0.805

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com