

CHEMLUBE® FBX

SYNTHETIC HIGH TEMPERATURE CHAIN LUBRICANT

Applications:

Chemlube FBX is a fully synthetic chain lubricant designed for use in high temperature applications. Chemlube FBX gives extended life in the temperature range to ~500°F (260°C) and will result in lower amount of carbon, gum or sludge deposits. This chain oil has outstanding wetting and spreading properties. With these properties, Chemlube FBX yields savings in maintenance dollars.

Application Tips: Lubrication points include steel belts, carpets of calibrated rollers, heating platens; roller bar chains; contact pressure and aligning chains; and beds of roller chains. In these applications it is necessary to cover the belts, chains, roller bars and slide rails with the proper film of oil.

Typical Industrial Applications:

- Single & Double Presses
- Tunnel / Lap / Tray Ovens
- High Speed Can Lines
- Lithographic Chains
- Oven Slides & Gears
- Conveyor Roller Ball Bearing Chains
- Fiberglass Processing
- Wood Processing
- Coating Ovens Automotive Industry

Performance Benefits:

- Superior resistance to wear
- Excellent high temperature corrosion-oxidation stability
- Reduced maintenance cost & cleanliness

TYPICAL PROPERTIES	TEST METHOD	Chemlube FBX
Viscosity @ 40°C,cSt	ASTM D2161	225
Viscosity @ 100°C,cSt	ASTM D2161	20.9
Viscosity Index	ASTM D2270	109
Flash Point, °C/°F	ASTM D92	237/459
Pour Point, °C/°F	ASTM D97	-42/-43
Copper Corrosion	ASTM D130	1b
Rust Prevention	ASTM D665	Pass
Lbs./Gal.	---	7.84
Specific Gravity	ASTM D1298	0.94

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com