

CHEMLUBE® 229A

DIESTER BASED COMPRESSOR OIL

Applications:

Chemlube 229A is designed for 8,000 hours of use in rotary vane and screw compressors. This product is specially formulated with diester base oils for use in a wide variety of air compressors.

Performance Benefits:

- Outstanding thermal and oxidative stability
- Will not varnish or form carbon deposits
- Wide operating temperature range
- Built in detergency action
- Extended drain intervals reduces oil deposal, thus increasing cost effectiveness

TYPICAL PROPERTIES	TEST METHOD	Chemlube 229A
ISO Grade	ASTM D2422	46
SAE Grade	SAE J-300	10W-20
Viscosity @ 40°C,cSt	ASTM D445	44.0
Viscosity @ 100°C,cSt	ASTM D445	7.0
Viscosity Index	ASTM D2270	116
Flash Point, °C/°F	ASTM D92	260/500
Pour Point, °C/°F	ASTM D97	-51/-60
Carbon Residue, %	ASTM D189	<0.02
Lbs./Gal.	---	7.51
Specific Gravity	ASTM D1298	0.90

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com