

## GENERIC SAE 40

### PREMIUM DIESTER-BASED COMPRESSOR LUBRICANT

#### Applications:

The Generic SAE 40 Compressor Oil is a fully synthetic lubricant specifically designed for use in upper cylinders and crankcases of reciprocating units. This compressor oil is formulated with premium diester base oils that extend the service life of the oil to 8,000 hours under good operating conditions.

#### Typical Industrial Applications:

- Reciprocating Compressors

#### Performance Benefits:

- Outstanding thermal and oxidative stability
- Will not varnish or form carbon deposits
- Wide operating temperature range
- Built-in detergency action
- Extended drain intervals reducing oil disposal and increasing cost effectiveness
- Caution: May affect some paint finishes, plastics and seals
- USDA H-2 authorized

**GEN. SAE40**

TYPICAL PROPERTIES	TEST METHOD	Generic SAE 40
ISO Grade	ASTM D2422	150
Viscosity @ 40°C,cSt	ASTM D445	146.5
Viscosity @ 100°C,cSt	ASTM D445	13.3
Viscosity Index	ASTM D2270	90
Flash Point, °C/°F	ASTM D92	271/520
Pour Point, °C/°F	ASTM D97	-34/-30
Copper Corrosion	ASTM D130	1a
Foaming Sequences I, II, III	ASTM D892	Nil
Demulsibility	ASTM D1401	Excellent
Evaporation, %	ASTM D972	0.90
Carbon Residue, %	ASTM D189	<0.02
Specific Gravity	ASTM D1298	0.94

03/10

#### HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

#### TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at [info@ultracheminc.com](mailto:info@ultracheminc.com)



900 Centerpoint Blvd.  
New Castle, DE 19720  
P.....302-325-9880  
F.....302-325-0335  
[info@ultracheminc.com](mailto:info@ultracheminc.com)