



## OMNILUBE® PC 100 FG Proofer Chain Lubricant

### Applications:

Omnilube PC 100 FG is a USP Grade White oil based chain lubricant designed for high humidity environments. This premium chain lubricant will not emulsify with water and provides excellent rust protection. Omnilube PC 100 FG has excellent metal wear resistance.

### Typical Industrial Applications:

- Proofer Boxes
- Conveyor Roller Ball Bearings
- Pin and Roller Chains
- Slides
- Gears
- Food Processing (NSF H-1 compliant)

### Performance Benefits:

- Superior resistance to metal wear
- Fortified to protect against oxidation and corrosion
- Reduced maintenance cost & cleanliness
- Superior lubricity provides an end to chain kinking or shortening
- USDA H-1 compliant

TYPICAL PROPERTIES	TEST METHOD	OMNILUBE PC 100 FG
ISO Grade	ASTM D2422	100
SAE Grade	SAE J-300	30
Viscosity @ 40° cSt	ASTM D445	100
Viscosity @ 100° C, cSt	ASTM D445	15
Viscosity Index	ASTM D2270	158
Flash Point, °C/°F	ASTM D92	188/370
Pour Point, °C/°F	ASTM D97	-15/5
Specific Gravity	ASTM D1298	0.88

2/11

#### HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

#### TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at [info@ultracheminc.com](mailto:info@ultracheminc.com)



900 Centerpoint Blvd.  
New Castle, DE 19720  
P.....302-325-9880  
F.....302-325-0335  
[info@ultracheminc.com](mailto:info@ultracheminc.com)

