



OMNILUBE[®] ULTRAGREEN[®] 32/46

BIODEGRADABLE LONG LIFE COMPRESSOR LUBRICANT

Applications:

Omnilube UltraGreen 32/46 is a readily biodegradable, non-hazardous ISO 32/46 grade compressor oil that meets or exceeds many compressor oil requirements. This oil is based on biodegradable base oil technology and is a direct replacement for petroleum based compressor oils. The product demonstrates excellent low and high temperature viscosity performance, premium oxidative stability and superior rust protection. Omnilube UltraGreen 32/46 gives an extended service life twice that of other biodegradable and petroleum compressor oils.

Typical Industrial Applications:

- Rotary Screw Compressors
- Centrifugal Compressors
- Vacuum Pumps
- Bearings
- Circulating Oil
- Environmentally Sensitive Applications

Performance Benefits:

- Longer service life
- Excellent low and high temperature performance
- Superior oxidative stability and rust protection
- Non-hazardous and Readily biodegradable

OMNILUBE[®]

TYPICAL PROPERTIES	TEST METHOD	Omnilube UltraGreen 32/46
ISO Grade	ASTM D2422	32/46
Viscosity @ 40°C,cSt	ASTM D445	39.6
Viscosity @ 100°C,cSt	ASTM D445	8.0
Viscosity Index	ASTM D2270	>200
Flash Point, °F	ASTM D92	>350
Pour Point, °C	ASTM D97	-37
Copper Corrosion	ASTM D130	1a
Rust Prevention; Distilled water	ASTM D665A	Pass
Demulsibility, oil/water/emulsion	ASTM D1401	40/40/0 (20)
RPVOT	ASTM D2272	300
Biodegradability CEC L-33 T-82, %	---	96
Specific Gravity	ASTM D1298	0.85

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com