

OMNILUBE® WO SV 22 and 100 USP GRADE WHITE OILS

ULTRACHEM

Applications:

Omnilube WO SV 22 and 100 are highly refined, purified USP Grade white mineral oils that are colorless, odorless, and tasteless. These premium white oils fully comply with USP and FDA requirements as per 21 CFR 172.878. Omnilube WO SV 22 is comparable to Witco's Carnation, Penreco's Drakeol 10, Mallet's Exalube, Ultra lube, and D-lube products. Omnilube WO SV 100 is comparable to Puretol Grade 55, Witco's Kadol, Penreco's Drakeol 600, Mallet's Prima lube and K-lube products.

Typical Industrial Applications:

- Bread Dividers
- Dough Troughs
- Use as a wipe down oil
- Use as a diluent oil
- Dust Suppression
- Textile Fiber Applications
- Lubricate, soften, smooth, moisturize, and add emolliency in the cosmetics and personal care industry

Performance Benefits:

- Edible
- Colorless, odorless, and tasteless
- USP Grade
- Complies with FDA CFR 172.878 3H

TYPICAL PROPERTIES	TEST METHOD	Omnilube WO SV 22	Omnilube WO SV 100
ISO Grade	ASTM D2422	22	100
Viscosity @ 40°C,cSt	ASTM D445	20	103
Neutrality	USP(latest rev.)	Pass	Pass
Readily Carbonizable Substances	USP(latest rev.)	Pass	Pass
Solid Paraffin	USP(latest rev.)	Pass	Pass
Limit of Polynuclear Compounds	USP(latest rev.)	Pass	Pass
Sulfur Compounds	USP XVII	Pass	Pass
Odor	LATM 092	None	None
Color, saybolt	ASTM D156	30 min.	30 min.
Breakdown Time, min.	LATM 017	40 min.	---
Pour Point	D97	---	-20
Specific Gravity, 25°C	D4052	0.85	0.86

Puretol* is a registered trademark of Petro-Canada.

12/13

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com