

PNEU MIST® 325 & PNEU MIST® 5075 SYNTHETIC LUBRICANTS FOR AIR LINE LUBRICATORS

Applications:

Pneu Mist 325 and 5075 are 100% premium synthetic air line lubricators. Pneu Mist 325 is FDA rated H-2 and designed for use at ambient and higher temperatures. Pneu Mist 5075 is designed for use in "cold room" applications. Pneu Mist 325 and 5075 are superior in eliminating downtime due to lubrication failure and sludge or varnish build-up when used in accordance with equipment manufacturers' recommendations.

Typical Industrial Applications:

- Pneumatic Equipment
- Pneumatic Systems
- Pneumatic Tools

Performance Benefits:

- Atomizes completely in all line lubricators
- Fully synthetic
- Prevents formation of gum, sludge, and varnish
- Dissolves oxidation products remaining from petroleum lubricants
- Prevents rust, prevents wear
- Minimizes downtime and saves maintenance dollars
- Compatible with plastics and synthetic rubber
- Keeps O-rings and seals soft
- Pneu Mist 325: USDA H-2 authorized

Pneu Mist is not compatible with petroleum-based lubricants and should not be mixed. All systems should be as free of petroleum as possible.

TYPICAL PROPERTIES	TEST METHOD	Pneu Mist 325	Pneu Mist 5075
ISO Grade	ASTM D2422	100	32
SAE Grade	SAE J-300	50	20
Viscosity @ 40°C,cSt	ASTM D445	87.3	32.9
Viscosity @ 100°C,cSt	ASTM D445	15.2	7.1
Viscosity Index	ASTM D2270	184	187
Flash Point, °C/°F	ASTM D92	232/450	213/415
Pour Point, °C/°F	ASTM D97	-37/-35	-48/-55
Lbs./Gal.	---	8.1	8.2
Specific Gravity	ASTM D1298	0.97	0.98

03/10

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com