

ULTRACHEM® COOLANT PE and COOLANT 32 PE ROTARY SCREW COMPRESSOR LUBRICANTS

APPLICATIONS:

Ultrachem® Coolant PE and Coolant 32 PE are developed from a unique premium blend of polyalkylene glycol (PAG) and pentaerythritol esters, which together form an exceptional coolant and act to reduce oxidation and deposit formation. These Coolants offer excellent heat transfer properties, long life, high flash points, low evaporation, low volatility, and excellent hydrolytic stability. They do not form varnish deposits like petroleum or PAO oils. Ultrachem Coolant PE and Coolant 32 PE are the generic alternatives to Ingersoll Rand SSR Ultra Coolant® and Sullube® 32 respectively and give the equivalent service life of 8,000 hours in rotary screw compressors.

TYPICAL INDUSTRIAL APPLICATIONS:

- Rotary Screw Compressors

PERFORMANCE BENEFITS:

- 100% synthetic
- Wide temperature range
- Eliminates deposit formation
- Cost effective
- Eliminates seasonal oil changes
- Polyalkylene glycol/pentaerythritol ester blend
- Extended oil change intervals
- High flash points mean reduced fire hazards
- Waste disposal is minimized due to longer life

TYPICAL PROPERTIES	TEST METHOD	Ultrachem Coolant PE	Coolant 32 PE
ISO Grade	ASTM D2422	46	32/46
Viscosity @ 40°C,cSt	ASTM D445	45.4	40
Viscosity @ 100°C,cSt	ASTM D445	9.6	8.3
Viscosity Index	ASTM D2270	202	188
Flash Point, °C/°F	ASTM D92	220/526	265/509
Pour Point, °C/°F	ASTM D97	-51/-60	-48/-55
Auto-ignition, °C	ASTM E659	>390	>390
Foaming Sequences I, II, III	ASTM D892	< 10/0	< 10/0
Color	Visual	---	Green
Specific Gravity	ASTM D4052	0.99	0.99

Sullube 32® and SSR Ultra Coolant® are registered trademarks of Sullair and Ingersoll Rand respectively.

01/17

HEALTH & SAFETY

To obtain an SDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com