

## ULTRACHEM COOLANT 68 PE FOR ROTARY SCREW COMPRESSORS

### Applications:

Unlike many other rotary screw synthetic compressor oils, this lubricant has been developed from a unique blend of polyglycol and pentaerythritol esters, which together form an exceptional coolant and act to reduce oxidation and deposit formation.

This Coolant offer excellent heat transfer properties, long life, high flash points, low evaporation, low volatility, and excellent hydrolytic stability. It does not form varnish deposits like petroleum or PAO oils.

### Performance Benefits:

- Fully 100% synthetic
- Polyglycol/pentaerythritol ester blend
- Wide temperature range
- Extended oil change intervals
- Eliminates deposit formation
- High flash points mean reduced fire hazards
- Waste disposal is minimized due to longer life
- Cost effective
- Three viscosity grades to choose from
- Eliminates seasonal oil changes

TYPICAL PROPERTIES	TEST METHOD	Ultrachem Coolant 68 PE
ISO Grade	ASTM D2422	68
Viscosity @ 40°C,cSt	ASTM D445	69
Viscosity @ 100°C,cSt	ASTM D445	11.9
Viscosity Index	ASTM D2270	170
Flash Point, °C/°F	ASTM D92	254/490
Pour Point, °C/°F	ASTM D97	-45/-50
Autoignition Temp °C/°F	E659	385/725
Foaming Sequence	D892	Nil
Specific Gravity	ASTM D1298	0.98

#### HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

#### TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at [info@ultracheminc.com](mailto:info@ultracheminc.com)

MADE  
IN  
USA



02/11  
900 CENTERPOINT BLVD.  
NEW CASTLE, DE 19720  
P: 302.325.9880  
F: 302.325.0335  
[INFO@ULTRACHEMINC.COM](mailto:INFO@ULTRACHEMINC.COM)