

ULTRACHEM RF12

PAG REFRIGERATION LUBRICANT

Applications:

This is a premium quality blend of polyalkylene glycols for hydrocarbon and gas compression applications. Ultrachem RF12 oil is custom blended with additives for oxidation stability, corrosion protection, and lubricity. Additional advantages include the ability to withstand hydrocarbon dilution. This oil is consistent with Frick specifications.

This lubricant is not compatible with mineral based oils like RF #2A, 3, 4, 5, 6, & 7

Typical Industrial Applications:

- Hydrocarbon & Compressed Gas Systems
- Reciprocating Compressors
- Cold Storage Facilities
- Ice Making machines

TYPICAL PROPERTIES	TEST METHOD	Ultrachem RF12
Viscosity @ 40°C,cSt	ASTM D445	150
Viscosity @ 100°C,cSt	ASTM D445	26.3
Viscosity, SUS @ 100°F		695
Flash Point, °C/°F	ASTM D92	227/440
Pour Point, °C/°F	ASTM D97	-37/-35
Service Temperature. °F		350
Specific Gravity	ASTM D1298	0.98
Recommended Applications		
Refrigerant		Hydrocarbon
Suction Temperature °F		N/A

12/2012

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com