

ULTRACHEM RF19

PAO REFRIGERATION LUBRICANT

Applications:

A high quality custom blended polyalphaolefin (PAO) synthetic hydrocarbon fluid which provides enhanced lubrication at both high and low temperatures, reduced volatility, and compatibility with mineral oils. This oil is consistent with Frick specifications.

Typical Industrial Applications:

- Low Temperature Ammonia Refrigeration Systems
- R-717
- Cold Storage Facilities
- Ice Making Machines

TYPICAL PROPERTIES	TEST METHOD	Ultrachem RF19
Viscosity @ 40°C,cSt	ASTM D445	68
Viscosity @ 100°C,cSt	ASTM D445	10.3
Viscosity, SUS @ 100°F		316
Flash Point, °C/°F	ASTM D92	260/501
Pour Point, °C/°F	ASTM D97	-55/-67
Service Temperature. °F		350
Specific Gravity	ASTM D1298	0.83
Recommended Applications		
Refrigerant		R-717
Suction Temperature °F		N/A

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



12/2012

900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com