

## **ULTRACHEM RF20**

### PAO REFRIGERATION LUBRICANT

#### **Applications:**

A high quality custom blended hydrocarbon fluid. This product has good chemical inertness, hydrolytic stability, and compatibility with mineral oil and mineral oil equipment. Ultrachem RF20 offers an alternative to traditional synthetic lubricants for low temperatures properties. This oil is consistent with Frick specifications.

#### **Typical Industrial Applications:**

- Ammonia Refrigeration Systems
- Cold Storage Facilities
- R-717
- Ice Making Machines

TYPICAL PROPERTIES	TEST METHOD	Ultrachem RF20
Viscosity @ 40°C,cSt	ASTM D445	65
Viscosity @ 100°C,cSt	ASTM D445	10
Viscosity, SUS @ 100°F		302
Flash Point, °C/°F	ASTM D92	260/501
Pour Point, °C/°F	ASTM D97	-55/-67
Service Temperature. °F		350
Specific Gravity	ASTM D1298	0.83
Recommended Applications		
Refrigerant		R-717
Suction Temperature °F		N/A

12/2012

#### **HEALTH & SAFETY**

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

#### **TECHNICAL SUPPORT**

To learn more about Ultrachem products and applications please contact us at [info@ultracheminc.com](mailto:info@ultracheminc.com)

900 Centerpoint Blvd.  
New Castle, DE 19720  
P.....302-325-9880  
F.....302-325-0335  
[info@ultracheminc.com](mailto:info@ultracheminc.com)