

ULTRACHEM PAG 40

Ultrachem PAG 40 is a high viscosity high performance water insoluble polyakylene glycol. Ultrachem PAG 40 is wax-free (free from solids) and will not form sludge, varnish, gum, or tar. This fluid also conforms to NSF H1 (21 CFR 178.3570).

Performance Benefits:

- High Viscosity Index – Wider Operating Temperature Range
- Low Friction of Coefficient
- Excellent Oxidative and Thermal Stability

TYPICAL PROPERTIES	TEST METHOD	Ultrachem PAG 40
Appearance	Visual	Bright & Clear
Color	ASTM D1500	<0.5
Viscosity @ 40°C,cSt	ASTM D445	370
Viscosity @ 100°C,cSt	ASTM D445	53
Viscosity Index	ASTM D2270	210
Flash Point, °C/°F	ASTM D92	232/450
Pour Point, °C/°F	ASTM D97	-40/-40
Water	ASTM D6304	< 50 ppm
Total Acid Number	ASTM D974	< 0.10 mg KOH/g
Specific Gravity	ASTM D1298	0.99

Caution: Not compatible with petroleum oils and synthetic hydrocarbons

03/13

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com