

VISCHEM® 362

SYNTHETIC HIGH TEMPERATURE GREASE

Applications:

Vischem 362 is a fully synthetic high temperature grease formulated for use where high thermal and oxidative stability is required. Vischem 362 has good load carrying capabilities and can be used for heavy or light loads.

Typical Industrial Applications:

- Business Machines
- Gear Boxes
- Gas Meters
- Tools
- Ball & Roller Bearings
- Cams/Slides/Gears
- Control Mechanisms
- Instruments
- Electric Motors
- Appliances
- Automotive
- Instrument Applications

Performance Benefits:

- Extreme long life
- Excellent oxidation stability, no deposits
- Outstanding thermal stability
- Wide useful temperature range, -40°F to 450°F

TYPICAL PROPERTIES	TEST METHOD	Vischem 362
NLGI Grade	---	2
Penetration Worked (60 strokes)	ASTM D217	270-300
Dropping Point, °F	ASTM D2265	500
Oil Separation, 24 hrs. at 100°C, %	ASTM D6184	3
Evaporation rate max., %	CTM	5
Water Washout	ASTM D1264	Nil
Normal Hoffman Bomb Oxidation		
100 hrs. PSI loss	---	0.0
500 hrs. PSI loss		0.3
Thickener	---	Cabosil
Base Oil	---	Synthetic
Base Oil Viscosity @ 210°F	ASTM D445	7.2
Base Oil Viscosity @ 100°F	ASTM D445	40
Base Oil Viscosity @ -40°C	ASTM D445	22,500
Flash Point, °C/°F	ASTM D92	246/475
Pour Point, °C/°F	ASTM D97	-54/-65

VISCHEM®

03/10

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com