

VISCHEM® 373 SYNTHETIC CHAIN LUBRICANT

Applications:

Vischem 373 is a fully synthetic chain lubricant for indoor and outdoor applications. Vischem 373 is formulated with a tackifier to prevent sling off and has excellent performance in applications that are problematic with water wash.

Typical Industrial Applications:

- Chains
- Gears
- Cams
- Slides
- Wire Rope

Performance Benefits:

- Extreme long life
- Excellent oxidation stability, no deposits
- Protects against moisture and salt atmospheres
- Tacky, will not sling off chains or gears
- Prevents wear
- High degree of solvency, cleans off old deposits
- Wide useful temperature range, -20°F to 275°F



TYPICAL PROPERTIES	TEST METHOD	Vischem 373
NLGI Grade	---	00
Penetration Worked (60 strokes)	ASTM D217	400-430
Dropping Point, °C/°F	ASTM D2265	168/335
Evaporation, 222 hrs. @ 210°F, %	---	0.9
Water Washout	ASTM D1264	Nil
Normal Hoffman Bomb Oxidation 500 hrs. PSI loss	---	6.0
Thickener	---	Lithium Stearate
Salt Spray, min. hrs.	---	50
Humidity cabinet, min. hrs.	---	500
Base Oil	---	Synthetic

03/10

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com